

All Prices are in Euro VAT excl.



Segmented Ceramic Clutch Disc 178 mm

Thickness (mm): 3.50 Product Code: TP8559
 Outside Diameter (mm): 178 Price for 1 pcs (EUR) 24.70
 Inside Diameter (mm): 40
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disc 212 mm

Thickness (mm): 3.50 Product Code: TP8656
 Outside Diameter (mm): 212 Price for 1 pcs (EUR) 25.50
 Inside Diameter (mm): 150
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disc 224 mm

Thickness (mm): 3.50 Product Code: TP8037
 Outside Diameter (mm): 224 Price for 1 pcs (EUR) 27.50
 Inside Diameter (mm): 150
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disc 231 mm

Thickness (mm): 3.50 Product Code: TP909C
 Outside Diameter (mm): 231 Price for 1 pcs (EUR) 30.30
 Inside Diameter (mm): 155
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disc 240 mm

Thickness (mm): 3.50 Product Code: TP2752-141
 Outside Diameter (mm): 240 Price for 1 pcs (EUR) 33.30
 Inside Diameter (mm): 162
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disc 264 mm

Thickness (mm): 3.50 Product Code: TPB10000
 Outside Diameter (mm): 264 Price for 1 pcs (EUR) 36.40
 Inside Diameter (mm): 164
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disc 276 mm

Thickness (mm): 3.50 Product Code: TP1166A
 Outside Diameter (mm): 276 Price for 1 pcs (EUR) 38.80
 Inside Diameter (mm): 164
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58

All Prices are in Euro VAT excl.



Ceramic Clutch Pad 67x36

Size (mm): 67.2 x 36.5

Rivet Diameter (mm): 9.6 +0.02

Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M

Certification: ISO/TS16949:2002, GB5764-98

Surface Hardness of button : 65 HRB

Price for 1 pcs (EUR):

Thickness (mm): 3.00

3.30

Thickness (mm): 3.25

3.50

Thickness (mm): 3.50

3.60

Thickness (mm): 4.00

3.80



Ceramic Clutch Pad 78x32

Size (mm): 78 x 32

Rivet Diameter (mm): 9.6 +0.02

Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M

Certification: ISO/TS16949:2002, GB5764-98

Surface Hardness of button : 65 HRB

Price for 1 pcs (EUR):

Thickness (mm): 3.50

3.60



Ceramic Clutch Pad 63x57

Size (mm): 63 x 57

Rivet Diameter (mm): 9.6 +0.02

Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M

Certification: ISO/TS16949:2002, GB5764-98

Surface Hardness of button : 65 HRB

Price for 1 pcs (EUR):

Thickness (mm): 3.50

4.30



Ceramic Clutch Pad Rivet

Size (mm): 9.40 x 9.17

Price for 1 pcs (EUR):

Steel Clutch Pad Rivet

0.40