



Segmented Ceramic Clutch Disk 178 mm

Thickness (mm): 3.50 Product Code: TP8559
 Outside Diameter (mm): 178
 Inside Diameter (mm): 40
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disk 212 mm

Thickness (mm): 3.50 Product Code: TP8656
 Outside Diameter (mm): 212
 Inside Diameter (mm): 150
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disk 224 mm

Thickness (mm): 3.50 Product Code: TP8037
 Outside Diameter (mm): 224
 Inside Diameter (mm): 150
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disk 231 mm

Thickness (mm): 3.50 Product Code: TP909C
 Outside Diameter (mm): 231
 Inside Diameter (mm): 155
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disk 240 mm

Thickness (mm): 3.50 Product Code: TP2752-141
 Outside Diameter (mm): 240
 Inside Diameter (mm): 162
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disk 264 mm

Thickness (mm): 3.50 Product Code: TPB10000
 Outside Diameter (mm): 264
 Inside Diameter (mm): 164
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Segmented Ceramic Clutch Disk 276 mm

Thickness (mm): 3.50 Product Code: TP1166A
 Outside Diameter (mm): 276
 Inside Diameter (mm): 164
 Certification: ISO/TS16949:2002, GB5764-98
 Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
 Friction Coefficient: 0.49-0.58



Ceramic Clutch Pad 67x36

Size (mm): 67.2 x 36.5
Rivet Diameter (mm): 9.6 +0.02
Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
Certification: ISO/TS16949:2002, GB5764-98
Surface Hardness of button : 65 HRB
Thickness (mm): 3.00
Thickness (mm): 3.25
Thickness (mm): 3.50
Thickness (mm): 4.00



Ceramic Clutch Pad 78x32

Size (mm): 78 x 32
Rivet Diameter (mm): 9.6 +0.02
Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
Certification: ISO/TS16949:2002, GB5764-98
Surface Hardness of button : 65 HRB
Thickness (mm): 3.50



Ceramic Clutch Pad 63x57

Size (mm): 63 x 57
Rivet Diameter (mm): 9.6 +0.02
Wearing rate: 0.05-0.12 10⁻⁷ cm³/N.M
Certification: ISO/TS16949:2002, GB5764-98
Surface Hardness of button : 65 HRB
Thickness (mm): 3.50



Ceramic Clutch Pad Rivet

Size (mm): 9.40 x 9.17
Steel Clutch Pad Rivet